























**Table11.** The results of large instances

	case	Primary network				Final network	
		Pre-Hub	$Opt_{cost}$	New hubs	$NO_P$	$Opt_{cost}$	t
50	50H5	3,4,7,8,13	81332.8	0	0	74915.30	1208.7
	50H6	3,4,7,8,41,45	76694.3	0	0	72515.23	1001.3
	50H7	4,7,8,9,26,37,45	69931.8	5	2,3,6	61122.65	985.2
	50H8	8,13,25,28,32,37,39,45	65334.1	2	12,17	61741.78	979.4
	50H9	13,18,23,26,28,32,37,45,48	61225.4	2	10,15	86959.11	944.6
	50H10	5,8,13,18,32,35,39,41,45,48	95132.5	4	1,27,38,42	102888.00	900.2
100	100H10	12,18,32,45,52,68,70,75,82,95	157222.8	5	4,5,10,14	198478.88	3241.5
	100H11	12, 15, 17, 19, 26, 32, 45,52, 67, 75,82	175325.7	2	5,8	151784.24	2999.4
	100H12	3,5,8,12,18,32,43,55,62,70,82,95	195342.0	0	0	162214.33	2514.6
	100H13	1,5,8,12,14,18,32,45,52,67,70,82,95	152340.3	3	22,40,58	201782.14	2387.8
	100H14	8,12,15,18,26,32,39,43,52,55,62,67,82,92	200142.3	1	35	199852.92	1978.2

We also compared the solution results with those had obtained by LINGO solver 15. Both GA and LING were run on the same system with the same parameters.

To perform the comparison of experiments, the population size  $P=20$  and the number of generation for GA are set to 30 and  $P_c = 0.8$ , and  $P_m = 0.2$  and the discount factors are assumed as  $\alpha = 0.1$ ,  $\gamma = \aleph = 0.4$ . Tables 12 gives the results of comparison experiment for two kinds of networks ( $n=10, 20$ ) with various hubs ( $P = 1,2,3,4,5$ ).

The third, fifth and seventh columns of the table 12 present set of hubs. The fourth and sixth columns of the table5 shows the corresponding costs from the results generated by our GA-based framework assuming the time as a deterministic and as a fuzzy parameter respectively. The eighth columns show the corresponding costs generated by LINGO. The running time of the three methods are given in the CPU (Time) columns which are measured in CPU seconds.

As we can see from table 12, the results demonstrate that the solutions of the fuzzy model because of more accurate seeking the solution space would be better than the model with deterministic parameters.

**Table12.** Effectiveness of the proposed algorithm

n	case	GA (Deterministic)		GA (Fuzzy)		LINGO (Fuzzy)		CPU(Time)		
		Hubs	Cost	Hubs	Cost	Hubs	Cost	$GA_{Dtr}$	$GA_{Fuzzy}$	LINGO
	10H1	3	6578.14	3	4223.66	3	4223.66	35.2	32.4	1300
10	10H2	3,6	7640.16	3,6	6017.29	3,6	6017.29	50.4	45.6	2070
	10H3	2,3,6	7737.06	2,3,5,6	7507.22	2,3,5,6	7507.22	52.9	45.0	2550
	10H4	2,3,6,7	7905.52	2,3,4,6,7	7528.98	2,3,4,6,7	7528.98	57.8	50.9	2490
	10H5	3,4,5,6,7	8755.83	3,4,5,6,7	7536.68	3,4,5,6,7	7536.68	60.2	56.4	2360
	20H1	12	11184.58	12	9986.24	12	9986.24	133.4	130.4	7821
	20H2	2,12	10772.30	2,7,12	9577.21	2,7,12	9577.21	184.6	165.5	10245
20	20H3	2,7,8	11246.05	2,3,5,7,8	11253.12	2,3,5,7,8	11253.12	194.8	179.7	9482
	20H4	2,5,7,12	10036.71	2,5,7,8,12	10025.98	2,5,7,8,12	10025.98	203.9	190.3	11254
	20H5	2,5,8,12,13	12544.03	2,5,8,12,13	12143.32	2,5,8,12,13	12143.32	213.0	200.8	8759

Moreover, comparison between the sixth and eighth columns of Table 7 illustrates that GA concept reaches optimal solution in significantly shorter CPU time compared to LINGO. Specifically, when the problem size is 20, the average

running time of GA method is 173s. LINGO solver achieves the same optimum values by an average running time of 9512 s. In addition, LINGO solver fails to efficiently solve large and complicated instances. It is due to the fact that LINGO solver achieves its optimal solution using the branch and bound procedure by examining nodes, where number of nodes becomes very large when the test problem size increases. Due to the memory requirements, LINGO solver is unavailable for large problem size.

## 5. Conclusions and future research

Among all of network parameters, travel time is one of the most important factors that cannot be considered deterministic since its values may vary because of traffic conditions, speed, and time of day, climate conditions, and land and road types. Due to the uncertainty of relevant data, the estimated travel time by automobile between two points has fuzzy features due to the measurement imprecision and perception (Yang et al. 2013).

In this paper we extended the model of the incapacitated hub location problem with fixed costs on networks under decentralized management (UHLP-DM) which was created by Vasconcelos et al. (2011). In our proposed extension, the time had been supposed as a fuzzy parameter and then the model was solved by genetic algorithm.

The results revealed that, because of exploring the more pieces of the solution space, using the fuzzy parameters contributed to more accurate system analysis. Using non-deterministic parameters has large practical real-world application in network design. Since, in the model, we sought to solve the large-sized UHLP-DM problem, it was solved using two genetic algorithms; the first one, GA1, was applied to create the initial network in which there were some pre-established hubs and the second one, GA2, was applied to find new hubs in such a network with regarding to the objective function. The proposed model was implemented for small-sized and large-sized problems using Matlab optimization software (R2013b v8.2) and it was run on the Windows 7 operating system with an Intel® Core™ i3-4030 processor and 4.00 GB of RAM. The described GA method used a binary encoding of the individuals and an appropriate objective function. However, the proposed GA algorithm surpasses the LINGO solver with respect to efficiency. It obtains optimal values in significantly less time than the LINGO solver for the same test problems. The proposed GA was also able to solve practical size problems that were out of reach for exact methods.

The presented solution is applicable to analyse the transport networks in free markets. Additionally, there are many other points for future research. Some of the points are:

- Consideration of demand in  $P_{ijkm}$  calculation.
- Consideration of the transferring cost in network cost calculation.
- Consideration the demand as a fuzzy parameter
- Creation of a new constraint to cover the demand in any hinterland.

## References

- Alumur S. A., Kara B. Y., and Karasan O. E. (2012). Multimodal hub location and hub network design, *Omega*, Vol. 40(6), pp. 927–939.
- Bashiri M., Mirzaei M. and Randall M. (2013). Modeling fuzzy capacitated p-hub center problem and a genetic algorithm solution, *Applied Mathematical Modelling*, Vol. 37, pp. 3513–3525.
- Campbell JF. and O’Kelly ME. (2012). Twenty-five years of hub location research, *Transp Sci*, Vol.46, pp. 153–169.
- Campbell J.F., Miranda J.R., Camargo R.S. and O’Kelly M.E. (2015). Hub Location and Network Design with Fixed and Variable Costs. *Annual Hawaii International Conference on System Sciences, Computer Society Press*, No. 48, pp. 1059-1067.
- Contreras I., Cordeau J.F. and Laporte G. (2011). Benders Decomposition for Large-Scale Uncapacitated Hub Location, *operation research*, Vol.6, pp. 1477-1490.
- Doerner K.F., Gendreau M., Greistorfer P., Gutjahr W., Hartl RF., and Reimann M. (2007). *Metaheuristics-progress in complex systems optimization*, Berlin: Springer.
- Domencich T. and McFadden D.L. (1975). *Urban travel demand: a behavioral analysis*, Amsterdam: North-Holland Publishing Co.
- Eraslan S. (2010). A genetic algorithm for the p-hub center problem with stochastic service level constraints, Dissertation, *Middle East technical university*.

- Ghaderi A. and Jabalameli M.S. (2013). Modeling the budget-constrained dynamic uncapacitated facility location–network design problem and solving it via two efficient heuristics: a case study of health care, *Math Comput Model*, Vol.57, pp. 382–400.
- Goldberg D.E. (1989). *Genetic Algorithms in Search, Optimization, and Machine Learning*, Reading, MA: Addison-Wesley.
- Haupt R.L. and Haupt S.E. (2004). *Practical Genetic Algorithms*, New York: Wiley.
- Hernández P., Alonso-Ayuso A., Bravo F., Escudero LF., Guignard M., Marianov V., and Weintraub A. (2012). A branch-and-cluster coordination scheme for selecting prison facility sites under uncertainty, *Comput Oper Res*, Vol.39, pp. 2232–2241.
- Holland J.H. (1975). *Adaptation in natural and artificial systems*, Michigan: University of Michigan Press.
- Hult E., Jiang H. and Ralph D. (2014). Exact computational approaches to a stochastic uncapacitated single allocation p-hub center problem, *Computational Optimization and Applications*, Vol.59, pp. 85-200.
- Kaur A. and Kumar A. (2011). A new method for solving fuzzy transportation problems using ranking function, *Applied Mathematical Modeling*, Vol.35, pp. 5652–5661.
- Kraticevic J., Stanimirović Zorica., Tosic D. and Filipović. (2005). Genetic algorithm for solving uncapacitated multiple allocation hub location problems, *Computing and Informatics*, Vol.24, pp. 415–426.
- Kwang D.r. and Lee H. (2005). *First Course on Fuzzy Theory and Applications*, Berlin: Springer.
- Nematian J. and Musavi M. (2016). Uncapacitated phub center problem under uncertainty, *Journal of Industrial and Systems engineering (Iranian Institute of Industrial Engineering)*, Vol. 9, pp. 23-39.
- O’Kelly M.E., Campbell J.F., Camargo R.S. and Miranda J.R. (2014). Multiple Allocation Hub Location Model with Fixed Arc Costs, *Geographical Analysis*, Vol.47, pp. 73–96.
- Ortuzar J.D. and Willumsen L.G. (1995). *Modelling transport*, New York, Wiley.
- Qin Z. and Gao Y. (2014). Uncapacitated p-hub location problem with fixed costs and uncertain flows, *Journal of Intelligent Manufacturing*, pp. 1-12.
- Rabbani M. and Kazemi M. (2015). Solving uncapacitated multiple allocation p-hub center problem by Dijkstra’s algorithm-based genetic algorithm and simulated annealing, *International Journal of Industrial Engineering Computations*, Vol.6, pp. 405–418.
- Rahmaniani R., Saidi M. and Ashouri H. (2013a). Robust Capacitated Facility Location Problem: Optimization Model and Solution Algorithms, *J Uncertain Syst* Vol.7(1), pp. 22–35.
- Rahmaniani R., Ghaderi A., Mahmoudi N. and Barzinepour S. (2013b). Stochastic p–robust uncapacitated multiple allocation p–hub location problems, *Int J Ind Syst Eng* Vol.14, pp. 296–314.
- Topcuoglu H., Corut F., Ermis M. and Yilmaz G. (2005). Solving the uncapacitated hub location using genetic algorithms, *Computers and Operational Research*, Vol.32, pp. 467–984.
- Vasconcelos A.D., Nassi C.D. and Lopes L.S. (2011). The uncapacitated hub location problem in networks under decentralized management, *Computers & Operations Research*, Vol.38, pp. 1656–1666.
- Waldemiro P.N. and Widmer J. (2013). *Compatibility of Long and Heavy Cargo Vehicles With the Geometric Design Standards of Brazilian Rural Roads and Highways*, New York: Wiley.
- Yang K., Liu Y.K. and Zhang X. (2011). Stochastic p-hub center problem with discrete time distributions, *Lecture Notes, Computer Science*, Vol.6676, pp. 182–191.

Yang K., Liu Y.K. and Yang G.Q. (2013). Solving fuzzy p-hub center problem by genetic algorithm incorporating local search, *Applied Soft Computing*, Vol.13(5), pp. 2624–2632.

Zarrinpoor N. and Seifbarghy M. (2011). A competitive location model to obtain a specific market share while ranking facilities by shorter travel time, *Int J Adv Manuf Technol* Vol.55, pp. 807–816.

Zanjirani Farahani R. , Hekmatfar M., Boloori Arabani A. and Nikbakhsh E. (2013). Hub location problems: A review of models, classification, solution techniques, and applications, *Computers & Industrial Engineering*, Vol.64, pp. 1096–1109.